



AVIDHIFI PELLERE™



"A feeling of never running out of steam"

The Pellere mirrors the innovative design of our flagship Pulsare II phono stage remaining fully balanced throughout and retaining the same high specification components, keeping noise and distortion exceptionally low across the entire audio spectrum, offering the same feeling of never 'running out of steam'.

XLR, RCA, Gain, Resistance and Capacitance are all easily adjustable via high quality switches on the base panel offering superb flexibility.

The passive RIAA circuit with Neumann HF correction including high-end capacitors, maintains linearity of reproduction; and an external regulated 300va power supply provides ample power to each channel separately. Fully manufactured within our high-grade facilities, including PCB assembly, helps ensure the Pellere allows you to not just listen, but experience the full potential that vinyl replay has to offer.

SPECIFICATIONS

Noise	< -81dB MM <-67dB MC
Distortion	< 0.001%
RIAA	5Hz - 70kHz +/-0.5dB
Gain	40dB - 50dB - 60dB - 70dB
Resistance	10R - 30R - 100R - 300R - 500R 1k - 5k - 10k - 47k
Capacitance	100pf - 200pf - 500pf - 1.5nf 10nf - 20nf
Power supply	Regulated with 300va transformer
Voltage input	100-240vac 50/60Hz 10 watts max. (depending on region)
Dimensions	290 x 240 x 100mm (WxDxH)
Net weight	Control unit - 3.8Kg (8.4lb) PSU - 6.4Kg (14lb)
Packaging	370 x 310 x 380mm (WxDxH)
Shipping weight	11.0Kg (24lb)



Bicton Industrial Park, Kimbolton, Huntingdon, Cambs. PE28 0LW ENGLAND
Tel: +44 (0)1480 869900 / Web: www.avidhifi.co.uk / Email: info@avidhifi.co.uk